

Helicopter Beam X-Triplex

Product information



This type of lifting beam is designed as a folding crossbeam. The lifting beam is designed with a double pullout per arm, allowing the attachment points to be adjusted in the length/width. A 4-part sling must be used between the lifting beam and the crane hook. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded beam construction providing good torsional stiffness. TRIPLEX model K is special designed to fit in the side direction of a truck.

Proof load: Usually 1,5 x WLL.

Material: Beam and plate of high-strength structural steel.

Marking: CE-marked, Working load limit (WLL), manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

62056520004500 (WLL 20 tons) can also be [rented](#) from us

Part code	WLL ton	Type	W max. mm	W mm	H, mm	L mm	L min. mm	L max. mm	S1 mm	S2 mm	Weight kg	Delivery time
62056502504200	2.5	Triplex 2,5	3,136	336	299	5,195	4,000	6,300	600	600	180	35
62056506004510	6	Triplex 6K*	2,391	371	330	4,120	2,430	4,830	600	600	190	35
62056510004510	10	Triplex 10K*	2,472	430	342	4,226	2,420	4,820	600	600	250	35
62056510004500	10	Triplex 10K	3,228	430	342	5,612	4,000	6,400	600	600	290	35
62056520004510	20	Triplex 20K*	1,805	460	370	3,939	2,210	-	600	450	420	35
62056520004500	20	Triplex 20K	2,603	460	370	5,867	4,000	-	600	600	540	35

Blueprint

