

## Helicopter Beam X-Triplex

### Product information

### CERTEX

This type of lifting beam is designed as a folding crossbeam. The lifting beam is designed with a double pullout per arm, allowing the attachment points to be adjusted in the length/width. A 4-part sling must be used between the lifting beam and the crane hook. Other lengths and working loads can be manufactured upon request.

**Design:** Lightweight welded beam construction providing good torsional stiffness. TRIPLEX model K is special designed to fit in the side direction of a truck.

**Test load:** 1.5 x WLL

... [Read more](#)



**Material:** Beam and plate of high-strength structural steel.

**Marking:** CE-marked, Working load limit (WLL), manufacturer, serial number, year of manufacturing, etc.


**Finish:** Yellow painted. Other treatments available on request.

**Note:** Top sling, separate slings and other accessories to be ordered separately.

62056520004500 (WLL 20 tons) can also be [rented](#) from us

## Helicopter Beam X-Triplex

### Blueprint



### Technical data

| Part code      | WLL ton | Type         | W max. mm mm | W mm | H mm | L mm  | L min. mm | L max. mm | S1 mm mm | S2 mm mm | Weight kg |
|----------------|---------|--------------|--------------|------|------|-------|-----------|-----------|----------|----------|-----------|
| 62056502504200 | 2.5     | Triplex 2,5  | 3,136        | 336  | 299  | 5,195 | 4,000     | 6,300     | 600      | 600      | 180       |
| 62056506004510 | 6       | Triplex 6K*  | 2,391        | 371  | 330  | 4,120 | 2,430     | 4,830     | 600      | 600      | 190       |
| 62056510004510 | 10      | Triplex 10K* | 2,472        | 430  | 342  | 4,226 | 2,420     | 4,820     | 600      | 600      | 250       |
| 62056510004500 | 10      | Triplex 10K  | 3,228        | 430  | 342  | 5,612 | 4,000     | 6,400     | 600      | 600      | 290       |
| 62056520004510 | 20      | Triplex 20K* | 1,805        | 460  | 370  | 3,939 | 2,210     | -         | 600      | 450      | 420       |
| 62056520004500 | 20      | Triplex 20K  | 2,603        | 460  | 370  | 5,867 | 4,000     | -         | 600      | 600      | 540       |