Lifting Solutions Group
Axel Johnson International

Helicopter Beam X-Triplex

Product information



This type of lifting beam is designed as a folding crossbeam. The lifting beam is designed with a double pullout per arm, allowing the attachment points to be adjusted in the length/width. A 4-part sling must be used between the lifting beam and the crane hook. Other lengths and working loads can be manufactured upon request.
Design: Lightweight welded beam construction providing good torsional stiffness. TRIPLEX model K is special designed to fit in the side direction of a truck.
Test load: 1.5 x WLL

... Read more

Material: Beam and plate of high-strength structural steel.
Marking: CE-mark, Working load limit (WLL), manufacturer, serial number, year of manufacturing, etc.
Finish: Yellow painted. Other treatments available on request.
Note: Top sling, separate slings and other accessories to be ordered separately.

62056520004500 (WLL 20 tons) can also be rented from us

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Helicopter Beam X-Triplex

Blueprint



Technical data

Part code	WLL ton	Type	W max. mm mm	W mm	H mm	L mm	L min. mm	L max. mm	S1 mm mm	S2 mm mm	Weight kg
62056502504200	2.5	Triplex 2,5	3,136	336	299	5,195	4,000	6,300	600	600	180
62056506004510	6	Triplex 6K*	2,391	371	330	4,120	2,430	4,830	600	600	190
62056510004510	10	Triplex 10K*	2,472	430	342	4,226	2,420	4,820	600	600	250
62056510004500	10	Triplex 10K	3,228	430	342	5,612	4,000	6,400	600	600	290
62056520004510	20	Triplex 20K*	1,805	460	370	3,939	2,210	-	600	450	420
62056520004500	20	Triplex 20K	2,603	460	370	5,867	4,000	-	600	600	540

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved