CERTEX | Lifting Solutions Group
Axel Johnson International

Swivel Eye / Eye Crosby S5

Product information



Design: Swivel with eyes equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- Other types and capacities up to 1250 t available on demand.

... *Read more*

Marking: CE-mark
Note: Always check before use if your steel wire rope is suitable for use with a swivel.
Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Swivel Eye / Eye Crosby S5

Blueprint



Technical data

Part code	WLL ton	Rope Ø mm	Swivel No	D mm	G mm	Q mm	R mm	S mm	T mm	Weight kg
422500300100	3	13	3-S-5	239	70	19.1	26.2	28.4	31.8	3.86
422500500100	5	16	5-S-5	249	76	25.4	32.5	31.8	31.8	5.13
422501500100	15	26	15-S-5	416	127	49.3	51.5	70	54	22.2
422502500100	25	-	25-S-5	565	152	57	58.5	98.5	60.5	59

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved