



## Swivel Eye / Hook Crosby S6

### Product information

**Design:** Swivel with eye and hook equipped with tapered roller thrust bearing.

**Features:**

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All hooks furnished with latches
- Other types and capacities up to 1250 t available on demand.

**Marking:** CE-marked

**Note:** Always check before use if your steel wire rope is suitable for use with a swivel.

**Warning:** Not to be used on demolition- (wrecking-) balls!

**Safety factor:** 5:1

Part code	Diameter mm	WLL ton	Rope Ø mm	Swivel No	E,	F,	G,	L	M mm	P mm	Q mm	R mm	S mm	T mm	V mm	Weight kg	Delivery time
422500300300	-	3	13	3-S-6	292	123	70,0	38,9	35,8	36,6	19,1	26,2	28,4	31,8	28,4	4.23	10
422500500300	-	5	16	5-S-6	332	160	76,0	49,3	42,9	46,0	25,4	32,5	31,8	31,8	36,6	6.46	10
422500850300	0	8.5	19	8-S-6	408	192	102	62,5	56,5	57,0	31,8	35,8	41,1	38,1	41,1	14.5	10
422501500300	-	15	26	15-S-6	540	263	127	71,5	61,0	76,0	49,3	51,5	70,0	54,0	60,5	28.6	10
422502500300	-	25	-	25-S-6	699	346	152	87,5	92,0	93,0	57,0	58,5	98,5	60,5	76,0	61	10

# Blueprint

