

Fixed Spreader Beams PALF

Product information



The PALF fixed spreader beam is designed for lifting loads while maintaining controlled spacing between lifting points. It is suited to industrial handling operations using synthetic slings, wire ropes or similar lifting accessories, with articulated rotating hooks supporting flexible load connection and alignment. Equipped with 2 articulated rotating hooks with forged safety latches.

Best used for:

- Repetitive lifting operations with a fixed lifting geometry.
- Handling loads with synthetic slings, chain slings or wire rope assemblies.

Product benefits:

- Fixed beam design supports repeatable lifting setups.
- Articulated rotating hooks improve load connection flexibility.
- Forged safety latches support secure hook engagement.
- Tear-resistant eyelets suit slings, cables and wire ropes.
- No structural welds and FEM 5 classification support demanding industrial use.
- Delivered with user's and maintenance manual and EC certificate of compliance [... Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Finish: RAL 1028 yellow

Standard: EN 13155

Fixed Spreader Beams PALF

Technical data

Part code	WLL ton	Length m	Weight kg
6205PALF1T1AC	1	1	25
6205PALF1T2AC	1	2	42
6205PALF1T3AC	1	3	72
6205PALF1T4AC	1	4	115
6205PALF1T5AC	1	5	170
6205PALF1T6AC	1	6	202
6205PALF1T7AC	1	7	280
6205PALF1T8AC	1	8	318
6205PALF2T1AC	2	1	28
6205PALF2T2AC	2	2	67
6205PALF2T3AC	2	3	111
6205PALF2T4AC	2	4	168
6205PALF2T5AC	2	5	238
6205PALF2T6AC	2	6	281
6205PALF2T7AC	2	7	371
6205PALF2T8AC	2	8	486
6205PALF3T1AC	3	1	37
6205PALF3T2AC	3	2	83
6205PALF3T3AC	3	3	134
6205PALF3T4AC	3	4	198
6205PALF3T5AC	3	5	278
6205PALF3T6AC	3	6	378
6205PALF3T7AC	3	7	495
6205PALF3T8AC	3	8	561
6205PALF4T1AC	4	1	48
6205PALF4T2AC	4	2	100
6205PALF4T3AC	4	3	158
6205PALF4T4AC	4	4	267
6205PALF4T5AC	4	5	368
6205PALF4T6AC	4	6	432
6205PALF4T7AC	4	7	573

Fixed Spreader Beams PALF

Technical data

Part code	WLL ton	Length m	Weight kg
6205PALF4T8AC	4	8	782
6205PALF5T1AC	5	1	56
6205PALF5T2AC	5	2	117
6205PALF5T3AC	5	3	183
6205PALF5T4AC	5	4	303
6205PALF5T5AC	5	5	420
6205PALF5T6AC	5	6	492
6205PALF5T7AC	5	7	693
6205PALF5T8AC	5	8	785
6205PALF6T1AC	6	1	61
6205PALF6T2AC	6	2	121
6205PALF6T3AC	6	3	215
6205PALF6T4AC	6	4	308
6205PALF6T5AC	6	5	425
6205PALF6T6AC	6	6	602
6205PALF6T7AC	6	7	699
6205PALF6T8AC	6	8	1,041
6205PALF8T1AC	8	1	76
6205PALF8T2AC	8	2	165
6205PALF8T3AC	8	3	250
6205PALF8T4AC	8	4	433
6205PALF8T5AC	8	5	525
6205PALF8T6AC	8	6	795
6205PALF8T7AC	8	7	930
6205PALF8T8AC	8	8	1,234
6205PALF10T1AC	10	1	91
6205PALF10T2AC	10	2	190
6205PALF10T3AC	10	3	288
6205PALF10T4AC	10	4	440
6205PALF10T5AC	10	5	687
6205PALF10T6AC	10	6	804

Fixed Spreader Beams PALF

Technical data

Part code	WLL ton	Length m	Weight kg
6205PALF10T7AC	10	7	1,096
6205PALF10T8AC	10	8	1,240