

Former with Thread Pin and Wing Nut Starcon

Product information



Starcon former with Starcon threaded pin and Starcon wing nut are used where it is necessary to attach the molds to the mold before concrete, placed around the element. The former are semi-circular and designed to hold the anchor in place in the mold. After casting the concrete element, the Starcon former can be removed from the head of the anchor, giving free access for the Starcon lifting eye to grab the anchor head and ensure a safe lift. The former are made of plastic and can be used several times, if they are cleaned of concrete residue with water after each use.

Applications: The former are used to ensure that the spherical anchor head is not covered by concrete during pouring.

Advantages: Quick coupling and disconnection of the spherical anchor.

Load capacities from 1.3S to 20S with durable, specially treated steel anchors for high reliability.

Can be recycled.

Load group: 1.3t – 20t

Technical information: CE marking in accordance with MD 2006/42 EC

Marking: Load group + S(Starcon)

Finish: Colour coded by load group

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) for information on the applicable delivery time.

Part code	Load grp. t	D mm	H mm	Packing Qty.	Delivery time
650311013001	1.0-1.3	60	30	1	10
650311025001	1.5-2.5	74	36	1	10
650311050001	3.0-5.0	94	46	1	10
650311075001	6.0-7.5	118	58	1	10
650311100001	8.0-10.0	118	58	1	10
650311150001	12.0-15.0	160	78	1	10
650311200001	16.0-20.0	160	78	1	10

Blueprint

