



Aluminium Gantry Crane foldable

Product information

Our range of lightweight portable gantries brings a new dimension to the professional lifting market. The portability, safe manual assembly and rigidity of the structure mean that it opens up a whole new market for the use of gantries with lifting applications such as confined space, rooftop, HVAC, lift-shaft, waste water, clean environments (food, hospitals etc.) and increasing availability from the hire industry.

Design: The gantry crane consists of four individual elements that can be assembled and disassembled in a few minutes. The height is adjustable so that the crane can also be placed in rooms with low ceilings.

Areas of applications:

- Moving and lifting of heavy loads.
- Building motors and driving applications in and out.
- Repair and maintenance of pumps.
- Loading trucks and trailers on and off.
- For use in workshops and on site.

Note: Can be delivered with capacity up to 3 tons, as well as custom-made solutions.

The gantry crane is delivered with a trolley, the hoist is purchased separately!

Part code	WLL ton	Model	Beam length m	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	L mm	W mm	X mm	Weight kg	Delivery time
60051110007	0.75	Mini	7	240	1,200	385	320	1230-2100	370	200	1615-2485	-	50	40	7,217	6,992	550	143	10
60051110008	0.75	Mini	8	240	1,200	385	320	1230-2100	370	200	1615-2485	-	50	40	8,217	7,992	550	153	10
60051120007	0.75	Standard	7	240	1,720	385	320	1680-3000	370	200	1470-1790	1470-1790	50	40	7,217	6,992	1,000	159	10
60051120008	0.75	Standard	8	240	1,720	385	320	1680-3000	370	200	1470-1790	1470-1790	50	40	8,217	7,992	1,000	168	10
60051130007	0.75	Maxi	7	240	2,295	385	320	2180-4000	370	200	1965-2285	1965-2285	50	40	7,217	6,992	1,500	175	10
60051130008	0.75	Maxi	8	240	2,295	385	320	2180-4000	370	200	1965-2285	1965-2285	50	40	8,217	7,992	1,500	184	10
60051110006	1	Mini	6	240	1,200	385	320	1230-2100	370	200	1615-2485	-	50	40	6,217	5,992	550	134	10
60051120006	1	Standard	6	240	1,720	385	320	1680-3000	370	200	1470-1790	1470-1790	50	40	6,217	5,992	1,000	149	10
60051130006	1	Maxi	6	240	2,295	385	320	2180-4000	370	200	1965-2285	1965-2285	50	40	6,217	5,992	1,500	165	10
60051110002	1.5	Mini	2	240	1,200	385	320	1230-2100	370	200	1615-2485	-	50	40	2,217	1,992	550	96	10
60051110003	1.5	Mini	3	240	1,200	385	320	1230-2100	370	200	1615-2485	-	50	40	3,217	2,992	550	105	10
60051120002	1.5	Standard	2	240	1,720	385	320	1680-3000	370	200	1470-1790	1470-1790	50	40	2,217	1,992	1,000	111	10
60051110004	1.5	Mini	4	240	1,200	385	320	1230-2100	370	200	1615-2485	-	50	40	4,217	3,992	550	115	10
60051120003	1.5	Standard	3	240	1,720	385	320	1680-3000	370	200	1470-1790	1470-1790	50	40	3,217	2,992	1,000	121	10
60051110005	1.5	Mini	5	240	1,200	385	320	1230-2100	370	200	1615-2485	-	50	40	5,217	4,992	550	124	10
60051130002	1.5	Maxi	2	240	2,295	385	320	2180-4000	370	200	1965-2285	1965-2285	50	40	2,217	1,992	1,500	127	10
60051120004	1.5	Standard	4	240	1,720	385	320	1680-3000	370	200	1470-1790	1470-1790	50	40	4,217	3,992	1,000	130	10
60051130003	1.5	Maxi	3	240	2,295	385	320	2180-4000	370	200	1965-2285	1965-2285	50	40	3,217	2,992	1,500	137	10
60051120005	1.5	Standard	5	240	1,720	385	320	1680-3000	370	200	1470-1790	1470-1790	50	40	5,217	4,992	1,000	140	10
60051130004	1.5	Maxi	4	240	2,295	385	320	2180-4000	370	200	1965-2285	1965-2285	50	40	4,217	3,992	1,500	146	2
60051130005	1.5	Maxi	5	240	2,295	385	320	2180-4000	370	200	1965-2285	1965-2285	50	40	5,217	4,992	1,500	156	10

Blueprint

