



Weld-on Lifting Point TAPSK

Product information

TAPSK weld-on sling point, edge fastening, in working load limits of 3,0 - 8,0 t.

Features: 180° swing.

Marking: CE-marked, UKCA-marked

Finish: Red painted.




Safety factor: 4:1

Grade: 8

Part code	Code	WLL ton	EWL mm	a mm	b mm	c mm	Ø d	l mm	Weight kg	Delivery time
42150380703100	TAPSK 3	3.15	53	12	56	50	18	53	1.01	2
42150380705100	TAPSK 5	5.3	63	15	67	60	22	63	1.84	10
42150380708100	TAPSK 8	8	68	20	80	70	26	68	3.14	10

Technical data

Kind of attachment



Number of pieces

1

1

2

2

2

3 o. 4

3 o. 4

Inclination angle

0°

0°

0°

0°-45°

45°-60°

0°-45°

45°-60°

WLL

WLL

WLL

WLL

WLL

WLL

WLL

Code

t

t

t

t

t

t

t

TAPSK 3

3,15

3,15

6,3

4,45

3,15

6,7

4,75

TAPSK 5

5,3

5,3

10,6

7,5

5,3

11,2

8

TAPSK 8

8

8

16,0

11,2

8

17

11,8

Blueprint

