

Special Master Link Assembly Pewag VAW

Product information



VAW For pewag connex and welded system. For assembling 3- and 4-leg chains with connex links CW, when shortening hooks are to be assembled separately, and for slings with thimble eyes.

For use in rope slings please consider that load capacity is listed according to EN 1677-4 with safety factor 4.

For assembling of welded slings with BW by pewag.

[... Read more](#)

Material: High duty grade 10

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type

Temperature range: -40°C up to +380°C

Finish: Orange powder coated


Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Special Master Link Assembly Pewag VAW

Blueprint



Technical data

Part code	Code	WLL ton	EWL	Consisting of	Use for hook DIN15401 Nr	Double hook DIN 15402 no.	e mm	t mm	w mm	Weight kg
402104110330	VAW 19/20	41.1	625	AW 50 + 2 MW 36	32	40	625	350	190	31.51
402104740330	VAW 22	47.4	690	AW 50 + 2 AW 45	32	40	690	350	190	42.19
402105800330	VAW 26	58	750	AW 56 + 2 AW 50	32	40	750	400	200	56.4
402108500330	VAW 32	85	860	AW 72 + 2 AW 56	50	63	860	460	250	99.02