



Master Link Assembly Pewag VSAW 1

Product information

VSAW is designed for assembling of welded chain slings with transition links BW by pewag. For assembling of chain slings with Connex CW.

Extra-large internal ring dimensions that are suitable for single hooks according to DIN 15401 no. 50/100 or for double hooks according to DIN 15402 no. 63/125 are yet another outstanding feature of these products.

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

| Part code | Code | WLL | EWL | Consisting of | Double hook DIN 15402 no. | Can be used up to single hook acc. to DIN 15401 no. | d | e | s | t | w | Weight | Delivery time |
|--------------|---------------|------|-----|---------------|---------------------------|---|----|-----|----|-----|-----|--------|---------------|
| | | ton | | | | | mm | mm | mm | mm | mm | kg | |
| 402101600360 | VSAW 1-19 | 16 | 460 | SAW 40 | 63 | 50 | 40 | 460 | 32 | 460 | 250 | 13.12 | 2 |
| 402102240360 | VSAW 1-22 | 22.4 | 500 | SAW 45 | 63 | 50 | 45 | 500 | - | 500 | 250 | 17.8 | 2 |
| 402104000361 | VSAW 1-32 320 | 40 | 800 | SAW 60 | 125 | 100 | 60 | 800 | 54 | 800 | 320 | 48 | 10 |

Blueprint

