



## Master Link Assembly Pewag VSAW 1

### Product information

VSAW is designed for assembling of welded chain slings with transition links BW by pewag. For assembling of chain slings with Connex CW.

Extra-large internal ring dimensions that are suitable for single hooks according to DIN 15401 no. 50/100 or for double hooks according to DIN 15402 no. 63/125 are yet another outstanding feature of these products.

**Material:** High duty grade 10.

**Marking:** According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

**Temperature range:** -40°C up to +380°C.

**Finish:** Orange powder coated.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

| Part code    | Code          | WLL  | EWL | Consisting of | Double hook DIN 15402 no. | Can be used up to single hook acc. to DIN 15401 no. | d  | e   | s  | t   | w   | Weight | Delivery time |
|--------------|---------------|------|-----|---------------|---------------------------|---|----|-----|----|-----|-----|--------|---------------|
|              |               | ton  |     |               |                           |   | mm | mm  | mm | mm  | mm  | kg     |               |
| 402101600360 | VSAW 1-19     | 16   | 460 | SAW 40        | 63                        | 50  | 40 | 460 | 32 | 460 | 250 | 13.12  | 2             |
| 402102240360 | VSAW 1-22     | 22.4 | 500 | SAW 45        | 63                        | 50  | 45 | 500 | -  | 500 | 250 | 17.8   | 2             |
| 402104000361 | VSAW 1-32 320 | 40   | 800 | SAW 60        | 125                       | 100   | 60 | 800 | 54 | 800 | 320 | 48     | 10            |

Blueprint

