Lifting Solutions Group
Axel Johnson International

Fast Connector Socket FCS - with bolt

Product information



Forged clevis fittings with bolt, nut and cutterpin for fast connection of steel wire rope. Connector shall be used with non-rotating or cat 1. rotation resistant wire rope only.

The connector has to be moulded/casted on the steel wire rope with wirelock resin

... *Read more*


Features: Designed for use with mobile cranes.
Material: Quenched and tempered cast steel.
Finish: Blue painted or hot dip galvanized.
Warning: Compare the spelter's and the wire rope's minimum breaking load.

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Fast Connector Socket FCS - with bolt

Blueprint



Technical data

Part code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	TB mm mm	TL mm mm	Weight kg
122101300155	FCS 701 B	11-13	20	Painted	62	61	27	15	25	12	25	50	33	49	46	80	150	1.6

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved